



# NTN BEARING CORP.OF AMERICA



1.181 Inch | 30 Millimeter x 2.441 Inch | 62 Millimeter x 0.787 Inch | 20 Millimeter SKF NUP 2206 ECP/C3 Cylindrical Roller Bearings

Bearing No. NUP 2206 ECP/C3

NUP 2206 ECP/C3 Bearing 2D drawings and 3D CAD models

Category	Cylindrical Roller Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	0.276
EAN	7316577031396
Product Group	B04144
Bore Profile	Straight
Cage Material	Polymer
Precision Class	RBEC 1   ISO P0
Number of Rows of Rollers	Single Row
Separable	No
Rolling Element	Cylindrical Roller Bearing
Profile	Complete with Outer and Inner Ring
Snap Ring	No
Internal Clearance	C3-Loose
Retainer	Yes
Relubricatable	Yes
Inch - Metric	Metric
Other Features	High Capacity   1 Rib Inner Ring with Side Plate   2 Rib Outer Ring   Cage on Outer Ring ID
Long Description	30MM Bore; Straight Bore Profile; 62MM Outside



# NTN BEARING CORP.OF AMERICA

	Diameter; 20MM Width; Polymer Cage Material; RBEC 1   ISO P0; Single Row; Not Separable; No Snap Ring; Relubricatable; C3-Loose Internal Clearance; Reta
Category	Cylindrical Roller Bearing
UNSPSC	31171547
Harmonized Tariff Code	8482.50.00.00
Noun	Bearing
Manufacturer URL	<a href="http://www.skf.com">http://www.skf.com</a>
Manufacturer Item Number	NUP 2206 ECP/C3
Weight / LBS	0.609
d	1.181 Inch   30 Millimeter
D	2.441 Inch   62 Millimeter
B	0.787 Inch   20 Millimeter
bore diameter:	30 mm
precision rating:	RBEC 1 (ISO Class Normal)
outside diameter:	62 mm
maximum rpm:	14000 RPM
overall width:	20 mm
bearing material:	Steel
flanges:	(4) Flanges, Two-Piece Inner Ring
cage material:	Polyamide
bore type:	Straight
finish/coating:	Uncoated
number of rows:	1
closure type:	Open
internal clearance:	C3
application:	Piston Type Machines, Rolling Mills, Spindles/Machine Tools



## NTN BEARING CORP.OF AMERICA

ring separation:	Separable Ring
outer ring width:	20 mm
operating temperature range:	Maximum of +300 ° F
fillet radius:	1 mm
dynamic load capacity:	55 kN
series:	NUP22
static load capacity:	49 kN